

“automatically” are not specified by the user, i.e., are not performed “manually”, where the user specifies each action to perform. For example, a user filling out an electronic form by selecting each field and providing input specifying information (e.g., by typing information, selecting check boxes, radio selections, etc.) is filling out the form manually, even though the computer system must update the form in response to the user actions. The form may be automatically filled out by the computer system where the computer system (e.g., software executing on the computer system) analyzes the fields of the form and fills in the form without any user input specifying the answers to the fields. As indicated above, the user may invoke the automatic filling of the form, but is not involved in the actual filling of the form (e.g., the user is not manually specifying answers to fields but rather they are being automatically completed). The present specification provides various examples of operations being automatically performed in response to actions the user has taken.

**[0068]** Approximately—refers to a value that is almost correct or exact. For example, approximately may refer to a value that is within 1 to 10 percent of the exact (or desired) value. It should be noted, however, that the actual threshold value (or tolerance) may be application dependent. For example, in some embodiments, “approximately” may mean within 0.1% of some specified or desired value, while in various other embodiments, the threshold may be, for example, 2%, 3%, 5%, and so forth, as desired or as required by the particular application.

**[0069]** Concurrent—refers to parallel execution or performance, where tasks, processes, or programs are performed in an at least partially overlapping manner. For example, concurrency may be implemented using “strong” or strict parallelism, where tasks are performed (at least partially) in parallel on respective computational elements, or using “weak parallelism”, where the tasks are performed in an interleaved manner, e.g., by time multiplexing of execution threads.

**[0070]** Various components may be described as “configured to” perform a task or tasks. In such contexts, “configured to” is a broad recitation generally meaning “having structure that” performs the task or tasks during operation. As such, the component can be configured to perform the task even when the component is not currently performing that task (e.g., a set of electrical conductors may be configured to electrically connect a module to another module, even when the two modules are not connected). In some contexts, “configured to” may be a broad recitation of structure generally meaning “having circuitry that” performs the task or tasks during operation. As such, the component can be configured to perform the task even when the component is not currently on. In general, the circuitry that forms the structure corresponding to “configured to” may include hardware circuits.

**[0071]** Various components may be described as performing a task or tasks, for convenience in the description. Such descriptions should be interpreted as including the phrase “configured to.” Reciting a component that is configured to perform one or more tasks is expressly intended not to invoke 35 U.S.C. § 112(f) interpretation for that component.

FIGS. 1A and 1B—Communication Systems

**[0072]** FIG. 1A illustrates a simplified example wireless communication system, according to some embodiments. It

is noted that the system of FIG. 1A is merely one example of a possible system, and that features of this disclosure may be implemented in any of various systems, as desired.

**[0073]** As shown, the example wireless communication system includes a base station **102A** which communicates over a transmission medium with one or more user devices **106A**, **106B**, etc., through **106N**. Each of the user devices may be referred to herein as a “user equipment” (UE). Thus, the user devices **106** are referred to as UEs or UE devices.

**[0074]** The base station (BS) **102A** may be a base transceiver station (BTS) or cell site (a “cellular base station”) and may include hardware that enables wireless communication with the UEs **106A** through **106N**.

**[0075]** The communication area (or coverage area) of the base station may be referred to as a “cell.” The base station **102A** and the UEs **106** may be configured to communicate over the transmission medium using any of various radio access technologies (RATs), also referred to as wireless communication technologies, or telecommunication standards, such as GSM, UMTS (associated with, for example, WCDMA or TD-SCDMA air interfaces), LTE, LTE-Advanced (LTE-A), 5G new radio (5G NR), HSPA, 3GPP2 CDMA2000 (e.g., 1×RTT, 1×EV-DO, HRPD, eHRPD), etc. Note that if the base station **102A** is implemented in the context of LTE, it may alternately be referred to as an ‘eNodeB’ or ‘eNB’. Note that if the base station **102A** is implemented in the context of 5G NR, it may alternately be referred to as ‘gNodeB’ or ‘gNB’.

**[0076]** As shown, the base station **102A** may also be equipped to communicate with a network **100** (e.g., a core network of a cellular service provider, a telecommunication network such as a public switched telephone network (PSTN), and/or the Internet, among various possibilities). Thus, the base station **102A** may facilitate communication between the user devices and/or between the user devices and the network **100**. In particular, the cellular base station **102A** may provide UEs **106** with various telecommunication capabilities, such as voice, SMS and/or data services.

**[0077]** Base station **102A** and other similar base stations (such as base stations **102B** . . . **102N**) operating according to the same or a different cellular communication standard may thus be provided as a network of cells, which may provide continuous or nearly continuous overlapping service to UEs **106A-N** and similar devices over a geographic area via one or more cellular communication standards.

**[0078]** Thus, while base station **102A** may act as a “serving cell” for UEs **106A-N** as illustrated in FIG. 1, each UE **106** may also be capable of receiving signals from (and possibly within communication range of) one or more other cells (which might be provided by base stations **102B-N** and/or any other base stations), which may be referred to as “neighboring cells”. Such cells may also be capable of facilitating communication between user devices and/or between user devices and the network **100**. Such cells may include “macro” cells, “micro” cells, “pico” cells, and/or cells which provide any of various other granularities of service area size. For example, base stations **102A-B** illustrated in FIG. 1 might be macro cells, while base station **102N** might be a micro cell. Other configurations are also possible.

**[0079]** In some embodiments, base station **102A** may be a next generation base station, e.g., a 5G New Radio (5G NR) base station, or “gNB”. In some embodiments, a gNB may be connected to a legacy evolved packet core (EPC) network